

Aggregate Optimization Chart

Production Gradation Report

PLANT #: **P-32**


Contractor: _____

Sample Date: **9/27/21**

Concrete Grade: **P1M**

Dates Test Represents: **9/28/2021** through **10/4/2021**

MDOT No.: _____



Superior Materials, LLC
30701 W. 10 Mile Rd.
Suite 500
Farmington Hills, MI 48336

<----- Verify this number is 100%

Agg. Class	Pit #	Source	Weight (ssd)	ft ³	Specific Gravity	Contribution %
CA	71-47	Presque Isle	950	5.81	2.62	30.9
IA	71-47	Presque Isle	870	5.32	2.62	28.3
2NS	95-013	Smelter Bay	1250	7.56	2.65	40.7
Total Wt			3070	18.69		100.0

Sieve	CA	IA	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	93.8	100.0	100.0	98.1	1.9	1.9
1"	27.4	100.0	100.0	77.5	20.5	22.5
3/4"	7.8	100.0	100.0	71.5	6.1	28.5
1/2"	3.0	76.2	100.0	63.2	8.2	36.8
3/8"	2.8	53.6	100.0	56.8	6.5	43.2
#4	2.7	15.0	96.2	44.3	12.5	55.7
#8	2.6	7.2	85.2	37.5	6.7	62.5
#16	2.6	4.6	71.2	31.1	6.4	68.9
#30	2.5	3.7	53.6	23.6	7.5	76.4
#50	2.4	3.2	26.0	12.2	11.4	87.8
#100	2.2	2.9	6.8	4.3	8.0	95.7
LBW	1.6	2.1	1.2	1.6	2.7	98.4


*Maximum % Retained must be above the 3/8" sieve.
 *Any two adjacent sieves must equal 10% except max.
 nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for each sieve except max.
 nom. max., #100 and #200 sieves.
 *% Retained must be at least 6% for the 1" sieve when
 a 2" max. size (nom. Max. 1.5") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations

Initial Production Sample (IPS)

Coarseness Factor: **69** Workability Factor: **38**

Coarseness Factor: **65** Workability Factor: **36**



Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	99.0	0.6	0.6
1"	84.0	15.3	16.0
3/4"	73.5	10.5	26.5
1/2"	65.2	8.2	34.8
3/8"	58.2	7.1	41.8
#4	44.1	14.1	55.9
#8	35.5	8.6	64.5
#16	29.1	6.4	70.9
#30	21.9	7.3	78.1
#50	9.6	12.2	90.4
#100	2.6	7.1	97.4
LBW	1.0	1.6	99.0

PREPARED BY:
SM, LLC Technical Service

Approved By: _____

Edw. C. Levy Co.

JMT
8911 W. Jefferson
Detroit, 48209
(313) 429-2429

Plant 958-JMT

Product 1022-2NS GR - Smelter Bay

Name/Title Doug Storey / QC Technician

Period: 09/26/2021 - 10/02/2021

Report Date 10/01/2021

Procedure	Sieve/Test	Result	Unit	2NS GR Spec
	3/8" (9.5mm)	100.0	%	100-100
	#4 (4.75mm)	96.2	%	95-100
	#8 (2.36mm)	85.2	%	65-95
	#16 (1.18mm)	71.2	%	35-75
	#30 (.6mm)	53.6	%	20-55
	#50 (.3mm)	26.0	%	10-30
	#100 (.15mm)	6.8	%	0-10
	#200 (75µm)	1.8	%	
	FM	2.61		2.6-3
	Wash Loss (#200/75µm)	1.2	%	0-3
	Total Moisture	3.6	%	

Plant 958-JMT

Product 7920-INTERMED AGG P1M LS PI

Name/Title Doug Storey / QC Technician

Period: 09/26/2021 - 10/02/2021

Report Date 10/01/2021

Procedure	Sieve/Test	Result	Unit	Intermed Agg P1M LS PI Target
	2" (50mm)	100.0	%	
	1 1/2" (37.5mm)	100.0	%	
	1" (25mm)	100.0	%	
	3/4" (19mm)	100.0	%	
	1/2" (12.5mm)	76.2	%	
	3/8" (9.5mm)	53.6	%	
	#4 (4.75mm)	15.0	%	
	#8 (2.36mm)	7.2	%	
	#16 (1.18mm)	4.6	%	
	#30 (.6mm)	3.7	%	
	#50 (.3mm)	3.2	%	
	#100 (.15mm)	2.9	%	
	#200 (75µm)	2.4	%	
	Wash Loss (#200/75um)	2.1	%	0-3
	Total Moisture	2.0	%	

Plant 958-JMT

Product 7919-COARSE AGG P1M LS PI

Name/Title Doug Storey / QC Technician

Period: 09/26/2021 - 10/02/2021

Report Date 10/01/2021

Procedure	Sieve/Test	Result	Unit	Coarse Agg P1M LS PI Target
	2" (50mm)	100.0	%	
	1 1/2" (37.5mm)	93.8	%	
	1" (25mm)	27.4	%	
	3/4" (19mm)	7.8	%	
	1/2" (12.5mm)	3.0	%	
	3/8" (9.5mm)	2.8	%	
	#4 (4.75mm)	2.7	%	
	#8 (2.36mm)	2.6	%	
	#16 (1.18mm)	2.6	%	
	#30 (.6mm)	2.5	%	
	#50 (.3mm)	2.4	%	
	#100 (.15mm)	2.2	%	
	#200 (75µm)	1.8	%	
	Wash Loss (#200/75um)	1.6	%	0-2
	Total Moisture	2.4	%	

Aggregate Optimization Chart

Production Gradation Report

PLANT #: **P-35**

Contractor: _____

Sample Date: **9/27/21**


Concrete Grade: **P1M**

Dates Test Represents: **9/28/2021** through **10/4/2021**

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	Contribution %
CA	58-003	Stoneco	1370	8.16	2.69	43.9
IA	58-003	Stoneco	550	3.28	2.69	17.6
N2S	81-093	Burnmeister	1200	7.26	2.65	38.5
Total Wt						100.0

Sieve	CA	IA	N2S	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	63.5	100.0	100.0	84.0	16.0	16.0
3/4"	29.2	100.0	100.0	68.9	31.1	31.1
1/2"	12.5	90.7	100.0	59.9	40.1	40.1
3/8"	7.5	70.2	100.0	54.1	45.9	45.9
#4	2.4	23.4	98.9	43.2	56.8	56.8
#8	1.7	7.7	87.8	35.9	64.1	64.1
#16	1.6	4.1	73.2	29.6	70.4	70.4
#30	1.5	2.9	52.6	21.4	78.6	78.6
#50	1.4	2.4	18.0	8.0	92.0	92.0
#100	1.3	2.2	3.4	2.3	97.7	97.7
LBW	1.1	2.0	0.8	1.1	98.9	98.9



Superior Materials, LLC
30701 W. 10 Mile Rd.
Suite 500
Farmington Hills, MI 48336

Sieve	CA	IA	N2S	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	63.5	100.0	100.0	84.0	16.0	16.0
3/4"	29.2	100.0	100.0	68.9	31.1	31.1
1/2"	12.5	90.7	100.0	59.9	40.1	40.1
3/8"	7.5	70.2	100.0	54.1	45.9	45.9
#4	2.4	23.4	98.9	43.2	56.8	56.8
#8	1.7	7.7	87.8	35.9	64.1	64.1
#16	1.6	4.1	73.2	29.6	70.4	70.4
#30	1.5	2.9	52.6	21.4	78.6	78.6
#50	1.4	2.4	18.0	8.0	92.0	92.0
#100	1.3	2.2	3.4	2.3	97.7	97.7
LBW	1.1	2.0	0.8	1.1	98.9	98.9


*Maximum % Retained must be above the 3/8" sieve.
*Any two adjacent sieves must equal 10% except max.
nom. max. #100 and #200 sieves.
*% Retained must be at least 4% for each sieve except max.
nom. max. #100 and #200 sieves.
*% Retained must be at least 8% for the 1" sieve when
a 2" max. size (nom. Max. 1.5") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations

Initial Production Sample (IPS)

Coarseness Factor: **72** Workability Factor: **36**

Coarseness Factor: **67** Workability Factor: **35**



Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	86.9	13.1	13.1
3/4"	76.1	10.8	23.9
1/2"	63.7	12.4	36.3
3/8"	56.2	7.5	43.8
#4	43.2	13.0	56.8
#8	34.7	8.5	65.3
#16	27.5	7.2	72.5
#30	20.6	7.0	79.4
#50	9.0	11.6	91.0
#100	2.1	6.9	97.9
LBW	1.0	1.1	99.0

PREPARED BY:
SM, LLC Technical Service

Approved By:



Plant S35-Superior Romulus

Product 1022-2NS GR

Name/Title Doug Storey / QC Technician

Period: 09/26/2021 - 10/02/2021

Report Date 10/01/2021

Procedure	Sieve/Test	Result	Unit	2NS GR Spec
	3/8" (9.5mm)	100.0	%	100-100
	#4 (4.75mm)	98.9	%	95-100
	#8 (2.36mm)	87.8	%	65-95
	#16 (1.18mm)	73.2	%	35-75
	#30 (.6mm)	52.6	%	20-55
	#50 (.3mm)	18.0	%	10-30
	#100 (.15mm)	3.4	%	0-10
	#200 (75µm)	1.0	%	
	FM	2.66		2.6-3
AASHTO T11	-#200 (75um)	1.02	%	
	Wash Loss (#200/75um)	0.8	%	0-3
ASTM C566	Total Moisture	4.38	%	



Plant S35-Superior Romulus

Product 7920-INTERMED AGG P1M LS

Name/Title Doug Storey / QC Technician

Period: 09/26/2021 - 10/02/2021

Report Date 10/01/2021

Procedure	Sieve/Test	Result	Unit	Intermed Agg P1M LS Target
	2" (50mm)	100.0	%	
	1 1/2" (37.5mm)	100.0	%	
	1" (25mm)	100.0	%	
	3/4" (19mm)	100.0	%	
	1/2" (12.5mm)	90.7	%	
	3/8" (9.5mm)	70.2	%	
	#4 (4.75mm)	23.4	%	
	#8 (2.36mm)	7.7	%	
	#16 (1.18mm)	4.1	%	
	#30 (.6mm)	2.9	%	
	#50 (.3mm)	2.4	%	
	#100 (.15mm)	2.2	%	
	#200 (75µm)	2.0	%	
	Wash Loss (#200/75um)	2.0	%	0-3
ASTM C566	Total Moisture	2.37	%	



Plant S35-Superior Romulus

Product 7919-COARSE AGG P1M LS

Name/Title Doug Storey / QC Technician

Period: 09/26/2021 - 10/02/2021

Report Date 10/01/2021

Procedure	Sieve/Test	Result	Unit	Coarse Agg P1M LS Target
	2" (50mm)	100.0	%	
	1 1/2" (37.5mm)	100.0	%	
	1" (25mm)	63.5	%	
	3/4" (19mm)	29.2	%	
	1/2" (12.5mm)	12.5	%	
	3/8" (9.5mm)	7.5	%	
	#4 (4.75mm)	2.4	%	
	#8 (2.36mm)	1.7	%	
	#16 (1.18mm)	1.6	%	
	#30 (.6mm)	1.5	%	
	#50 (.3mm)	1.4	%	
	#100 (.15mm)	1.3	%	
	#200 (75µm)	1.2	%	
	Wash Loss (#200/75um)	1.1	%	0-2
ASTM C566	Total Moisture	1.45	%	