

Aggregate Optimization Chart

Production Gradation Report

PLANT #: **P-103**

Sample Date: 5/19/25

Concrete Grade: **DM, 4500HP**

Contractor: _____

Dates Test Represents: 5/20/2025 through 5/26/2025

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
6AA	58-003	Stoneco	1350	8.04	2.69	45.8
26A	58-003	Stoneco	450	2.68	2.69	15.3
2NS	63-114	Highland	1150	6.95	2.65	39.0
Total Wt			2950	17.68		100.0

<----- Verify this number is 100%

Sieve	6AA	26A	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	100.0	100.0	100.0	100.0	0.0	0.0
3/4"	82.7	100.0	100.0	92.1	7.9	7.9
1/2"	39.2	99.2	100.0	72.1	20.0	27.9
3/8"	18.6	86.5	100.0	60.7	11.4	39.3
#4	2.8	11.7	99.2	41.7	19.0	58.3
#8	1.3	2.5	85.6	34.3	7.4	65.7
#16	1.2	1.6	67.6	27.1	7.2	72.9
#30	1.0	1.4	49.5	20.0	7.2	80.0
#50	1.0	1.2	22.3	9.3	10.6	90.7
#100	0.9	1.2	3.0	1.8	7.6	98.2
LBW	0.8	1.0	0.4	0.7	1.1	99.3

*Maximum % Retained must be above the 3/8" sieve.

*Any two adjacent sieves must equal 10% except max.,

nom. max., #100 and #200 sieves.

*% Retained must be at least 4% for each sieve except max.,

nom. max., #100 and #200 sieves.

*% Retained must be at least 4% for the 3/4" sieve when

a 1.5" max. size (nom. Max. 1.0") aggregate is used.



Superior Materials, LLC
30701 W. 10 Mile Rd.
Suite 500
Farmington Hills, MI 48336


Production Gradation ☐ Batch Plant Gradations ☒ Aggregate Supplier Gradations

Adjusted WF Initial Production Sample (IPS)

Coarseness Factor:	60	Workability Factor:	34	36.8
---------------------------	-----------	----------------------------	-----------	-------------

Coarseness Factor:	61
---------------------------	-----------

Workability Factor:	36
----------------------------	-----------



Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	99.3	0.7	0.7
3/4"	89.2	10.1	10.8
1/2"	70.7	18.5	29.3
3/8"	60.7	10.0	39.3
#4	44.4	16.3	55.6
#8	35.9	8.5	64.1
#16	27.3	8.6	72.7
#30	19.1	8.2	80.9
#50	7.4	11.7	92.6
#100	1.9	5.6	98.1
LBW	0.7	1.2	99.3

PREPARED BY:
SM, LLC Technical Service

Approved BY:

Aggregate Optimization Chart

Production Gradation Report

PLANT #: **p11**

Sample Date: **5/19/25**

Dates Test Represents: **5/20/2025** through **5/26/2025**

Concrete Grade: **DM, 4500HP**

Contractor: _____

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
6AA	71-47	Presque Isle	1450	8.87	2.62	49.9
26A	71-47	Presque Isle	305	1.87	2.62	10.5
2NS	63-115	Ray Rd	1150	6.95	2.65	39.6
Total Wt			2905	17.69		100.0

<----- Verify this number is 100%

Sieve	6AA	26A	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	96.8	100.0	100.0	98.4	1.6	1.6
3/4"	77.6	100.0	100.0	88.8	9.6	11.2
1/2"	30.2	97.5	100.0	64.9	23.9	35.1
3/8"	15.1	87.1	100.0	56.3	8.6	43.7
#4	3.5	24.8	97.8	43.1	13.2	56.9
#8	2.4	9.3	79.3	33.6	9.5	66.4
#16	2.2	4.9	62.5	26.4	7.2	73.6
#30	2.0	3.8	46.1	19.6	6.7	80.4
#50	1.9	3.4	24.2	10.9	8.8	89.1
#100	1.8	3.1	5.0	3.2	7.7	96.8
LBW	1.5	2.6	0.8	1.3	1.9	98.7

*Maximum % Retained must be above the 3/8" sieve.
 *Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for the 3/4" sieve when a 1.5" max. size (nom. Max. 1.0") aggregate is used.




Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336

Production Gradation ☐ Batch Plant Gradations ☒ Aggregate Supplier Gradations

Adjusted WF Initial Production Sample (IPS)

Coarseness Factor:	66	Workability Factor:	34	36.1
---------------------------	-----------	----------------------------	-----------	-------------



Coarseness Factor:		62	
Workability Factor:		36	
Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	100.0	0.0	0.0
3/4"	95.0	5.0	5.0
1/2"	72.3	22.8	27.7
3/8"	60.4	11.8	39.6
#4	42.6	17.8	57.4
#8	36.0	6.6	64.0
#16	29.5	6.5	70.5
#30	20.3	9.2	79.7
#50	9.5	10.8	90.5
#100	3.4	6.1	96.6
LBW	1.3	2.1	98.7

PREPARED BY:
 SM, LLC Technical Service

Approved By: